

PERFORMANCE OF FOAM CONCRETE



A PROJECT REPORT

Submitted By,

GOKULAKANNAN HARI PRASATH N VIHASHINI

(710419103008) (710419103009) (710419103019)

In partial fulfilment for the award of the degree
Of

BACHELOR OF ENGINEERING

IN

CIVIL ENGINEERING

CHRIST THE KING ENGINEERING COLLEGE COIMBATORE,641104

ANNA UNIVERSITY: CHENNAI 600025

MAY 2023



Dr.M.JEYAKTMAR, M.E..Ph.D.
PRINCIPAL
CHRIST THE KING ENGINEERING COLLEGE,
Chikkarampalayam Village.
Karamadai, Menupalayam Taluk,
Colmbatore - 641-104.

BONAFIDE CERTIFICATE

Certified that this project report' PERFORMANCE OF FOAM CONCRETE" is the bonafide work of GOKULAKANNAN S, HARIPRASATH N, VIHASHINI who carried out the project work under my supervision.

SIGNATURE

Mr.S.KARTHIKM.E., HEAD OF THE DEPARTMENT

Department of civil engineering, Christ the king engineering college, Coimbatore- 641104 SIGNATURE

Mr.S.KARTHIK M.E.,

SUPERVISIOR

Department of civil engineering, Christ the king engineering college,

Coimbatore- 641104

Submitted for the viva voice on 23.05-2023

Internal examiner

External examiner



Dr.M.JEYARUMAR, M.E..Ph.D.
PRINCIPAL

CHRIST THE KING ENGINEERING COLLEGE, Uhikkarampalayam Village, Karamodai, Mettupatayam fatuk, Connoatore - 041-104.

ABSTRACT

This project work which has been carried out to study about the performance of foam concrete in order to analyze the strength properties of this concrete. Because the advanced and modern materials which plays a major role in these concrete industry. So we have tried to analyze the performance of these foam concrete by analysing the strength properties of these concrete by adding foaming agent and different composition.

By doing the same these properties and result obtained from the tests which are compared with the strength properties of ordinary Portland cement concrete has been done to understand the nature.

The project aims to investigate the mechanical properties like compressive strength and split tensile strength for grade of concrete. The specimens were tested at 7 days and 28 days.

In general concrete in strong in compression and weak in tensional property. The different applications of foam concrete where discussed in this study some of the advantages are thermal insulated, fire resistant, light weight etc,

To augment the properties of materials and improving their performances different materials which are need to be introduced, in which the foam concrete which has a light, strong, fire resistant, weather resistant, attractive, imperable material as needed.

KEYWORDS:

Foaming Agent, Thermal insulated, light weight, acoustic, foam concrete.

KARANGADAI COINTOATORE 641 104

Dr.M. JEVA KEMAR, M.E. Ph.D.
PRINCIPAL
CHRIST THE KING ENGINEERING COLLEGE,
Cuikkarampalayam Village,
Karamadai, Mertupalayam Taluk,
Colmbatore - 641 104.

CONCLUSION

With the addition of different volume of foaming agent from 0.02% to 0.04% and with 1% of super plasticizer & 0.8% of VMA by the weight of cement, the structural behavior of FOAM CONCRETE have been investigated. The following conclusions were drawn with reference to the results obtained in this investigation.

Workability of concrete decreases respectively by the increase in volume o fibers.

Even though the values get reduced, all the concrete mix we obtained are workable.

The maximum compressive strength of 33.92 N/mm² was obtaining at addition of foaming agent 0.03% of concrete, The percentage improvement of the compressive strength over the reference concrete is 5.66%

The maximum split tensile strength of 2.64 N/mm² was obtaining at addition of foaming agent 0.03% of concrete, The percentage improvement of the split tensile strength over the reference concrete is 3.94 %

The maximum flexural strength of 8.0 N/mm² was obtaining at addition of foaming agent 0.03% of concrete, The percentage improvement of the flexural strength over the reference concrete is 11.12 %

After this experimental investigation, We have to conclude that incorporation of foaming agent by 0.03% of concrete has increased the strengths at 28 days by 5.66 % in compression, 3.94 % in tension, and 11.12 % in flexure. Finally we had concluded that addition of foaming agent by 0.03% of concrete should optimum and incorporation of foaming agent should increase the flexural strength than the compressive and tensile strength.

COIMDATORE SAI 104

Dr.M. JEVARUMAR, M.E.Ph.D.

PRINCIPAL

CHRIST THE KING ENGINEERING COLLEGE,

Chikkarampalayam Village,

Karamada, Mettupalayam Taluk,

Coimbatore - 641 104.